

TECHNICAL DATA

| | |
|--|---|
| Composición / Composition Composition / Composizione | 100% PES |
| Peso / Poids Weight / Peso | 350 g/m ² - 10,3 oz/yd ² |
| Espesor / Épaisseur Thickness / Spessore | 0,46 mm - 0,018" |
| Ancho de rollo / Largeur rouleau Roll width / Larghezza del tessuto | 300 cm - 118" |
| Grado de apertura / Coefficient d'ouverture Openess Factor / Grado di apertura (%) | 100% Opac |
| Resistencia al fuego / Classement feu Fire classification / Resistenza al fuoco | Pass - NFPA701 UNI 9177 - Classe1 EN 13773 - Class1 |
| Resistencia a la luz / Résistance à la lumière Light Fastness / Resistenza alla luce (Blue scale) | 6 |

TOTAL OPACITY IN LARGE DIMENSIONS FOR OUTDOOR INSTALLATION

- 100% UV blocking. Totally opaque fabric for maximum privacy.
- Composed of 100% de Pes.
- A fabric with a textile appearance.
- Available for the following systems: Premium, Premium Plus, Fit Box, B-Box range, Q-Box range, Z-Box range, and Sliding pannel.
- Suitable for indoor installation.
- Effective thermal protection that reduces building energy consumption. White side facing outwards for optimum reflection of solar energy.



PROPERTIES



MAINTENANCE



CERTIFICATES

FABRICS CERTIFICATES



Contributing to Ecofriendly Building



BREEAM®

COMPANY & SYSTEMS CERTIFICATES



ISO 9001 50001
14001 45001

